



product details

**DULUX D/E 26 W/830**

Product description: DULUX D/E 26 W/830  
 Product code: 4050300327242  
 Quantity: Shipping carton box (VS) contains 10 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=DE&it\\_p=4050300327242](http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300327242)

Applications	
Suitable for indoor	Yes

Categorizations	
SEG number	8330196

Certificates & Standards	
EEl - Energy Label	B

General Description	
Rated lamp mercury content	2.6 mg
Base (standard designation)	G24q-3
Recycling	Yes

Technical - Electrical Data	
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Construction wattage	26 W
Nominal wattage (packaging)	26 W

Technical - Geometries	
Overall length	165.00 mm
Diameter	11.00 mm
Tube diameter	12 mm
Length with base excl. base pins/connect	149 mm
Length	165.00 mm
Length acc. to IEC standard	160 mm
Construction length	165.00 mm

Technical - Lifespan	
Rated lamp life time	20000 h
Nominal lamp life time	20000 h
Operation mode LLMF/LSF	50 Hz

Technical - Light Technical Data	
Nominal luminous flux	1800 lm
Rated color rendering index Ra	>=80
Luminous flux at 25 °C	1800 lm
Rated luminous flux	1800 lm
Luminous flux	1800 lm
Light color	830
Rated color temperature	3000 K
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX Warm White





product details

## DULUX D/E 26 W/830

### Technical - Light Technical Data

Color rendering group	1B
Color temperature	3000 K

### Technical - Temperatures

Rated ambient temp.w.max.luminous flux	25.0 °C
--	---------

### Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300327235	Folding carton box contains 1 Piece	52,000 mm x 36,000 mm x 179,000 mm	59,000 g (0,000 g)	0,233 Cubic dec.
4050300327242	Shipping carton box contains 10 Piece	141,000 mm x 183,000 mm x 141,000 mm	624,000 g (0,000 g)	2,893 Cubic dec.

These compact fluorescent lamps can be operated on battery, solar or ac power. They are suitable for high-voltage and low-voltage ranges. They can also be fully dimmed. Their dimensions and wattages are identical to those of the successful standard OSRAM DULUX D models. The fact that they can be used with separate electronic control gear means they can be connected to almost any type of power supply, including ac, batteries and solar cells. Major applications include dimming and battery-powered emergency lighting in department stores, office buildings and so on.

- Comfortable light in ECG operation
- Shortened base casing to prevent two-pin lamps being fitted in new D/E holders, but still still fits in old D/E holders