


DIN 933

ISO 4017

Kuusioruuvi, täyskierteinen
Hexagon screw, full thread
Болт с шестигранной головкой (с полной резьбой)
Kuusikantpolt, täiskeermeline



	M4	M5	M6	M8	M10	M12	M14	M16	M20	M24	M27	M30	M36
k	2,8	3,5	4	5,3	6,4	7,5	8,8	10	12,5	15	17	18,7	22,5
s	7	8	10	13	17	19	22	24	30	36	41	46	55

d	L (mm)	A4-70 2001	A4-80 20010	A2-70 4001	Zn 8.8 1057	HOT 8.8 5057	St 10.9 0056
M4	6				▲		
	8	▲	Ⓜ		▲		
	10	▲	Ⓜ		▲		
	12	▲	Ⓜ		▲		
	16	▲	Ⓜ		▲		
	20	▲	Ⓜ		▲		
	25	▲	Ⓜ		▲		
	30	▲	Ⓜ		▲		
	35				▲		
	40				▲		
	50		Ⓜ		▲		
M5	8				▲		
	10		▲		▲		
	12		▲	▲	▲		
	16		▲	▲	▲		
	20		▲	▲	▲		
	25		▲	▲	▲		
	30		▲	▲	▲		
	35		▲		▲		
	40		▲		▲		
	45		▲		▲		
	50				▲		
M6	60				▲		
	8				▲		
	10		▲		▲		▲
	12		▲	▲	▲		▲
	14				▲		
	16		▲	▲	▲		▲
	20		▲	▲	▲		▲
	25		▲	▲	▲		▲
	30		▲	▲	▲		▲
	35		▲	▲	▲		▲
	40		▲	▲	▲		▲
45		▲	Ⓜ	▲			
50		▲	▲	▲			
60		▲	▲	▲			
70				▲			
80				▲			
90				▲			
100				▲			

d	L (mm)	A4-70 2001	A4-80 20010	A2-70 4001	Zn 8.8 1057	HOT 8.8 5057	St 10.9 0056	
M8	10		▲		▲			
	12		▲	▲	▲	▲		
	16		▲	▲	▲	▲		
	20		▲	▲	▲	▲	▲	
	25		▲	▲	▲	▲	▲	
	30		▲	▲	▲	▲	▲	
	35		▲	▲	▲	▲	▲	
	40		▲	▲	▲	▲	▲	
	45		▲	▲	▲	▲	▲	
	50		▲	▲	▲	▲	▲	
	55					▲	Ⓜ	
	60		▲	▲	▲	▲	▲	
	65					▲		
	70		▲	▲	▲	▲	▲	
	75					▲		
	80		▲	Ⓜ	▲	▲	▲	
90		▲			▲	Ⓜ		
100		▲	▲	▲	▲	▲		
110					▲			
120		Ⓜ			▲			
140					▲			
160					▲			
M10	12			Ⓜ	▲			
	16		▲	▲	▲	▲		
	20		▲	▲	▲	▲	▲	
	25		▲	▲	▲	▲	▲	
	30		▲	▲	▲	▲	▲	
	35		▲	▲	▲	▲	▲	
	40		▲	▲	▲	▲	▲	
	45		▲	▲	▲	▲	▲	
	50		▲	▲	▲	▲	▲	
	55					▲		
	60		▲	▲	▲	▲	▲	
	65					▲		
	70		▲	Ⓜ	▲	▲	▲	
	75					▲	Ⓜ	
	80		▲	Ⓜ	▲	▲	▲	
	85					▲		
90		▲			▲	Ⓜ		
100		▲			▲	Ⓜ		
110					▲			

© Ferrometal 08/2015