

300 HSS DIN 338 STANDARD



DRIVE



EXECUTION

- Right-hand cutting, type N
- High-performance high-speed steel
- Short, cylindrical
- 118° conical section
- Diametral tolerance h8


FOR USE IN



APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

PACKAGING



against
surcharge

[151-152]

[152]

D ø mm	L2 mm	L1 mm	d ø mm		EAN 4016707...	
0,50	6	22	0,5	10	040016	300 000 050
0,60	7	24	0,6	10	040023	300 000 060
0,70	9	28	0,7	10	040030	300 000 070
0,80	10	30	0,8	10	040047	300 000 080
0,90	11	32	0,9	10	040054	300 000 090
1,00	12	34	1,0	10	040061	300 000 100
1,10	14	36	1,1	10	040078	300 000 110
1,20	16	38	1,2	10	040085	300 000 120
1,25	16	38	1,3	10	040092	300 000 125
1,30	16	38	1,3	10	040108	300 000 130
1,40	18	40	1,4	10	040115	300 000 140
1,50	18	40	1,5	10	040122	300 000 150
1,60	20	43	1,6	10	040139	300 000 160
1,70	20	43	1,7	10	040146	300 000 170
1,75	22	46	1,8	10	040153	300 000 175
1,80	22	46	1,8	10	040160	300 000 180
1,90	22	46	1,9	10	040177	300 000 190
2,00	24	49	2,0	10	040184	300 000 200
2,10	24	49	2,1	10	040191	300 000 210
2,20	27	53	2,2	10	040207	300 000 220
2,25	27	53	2,3	10	040214	300 000 225
2,30	27	53	2,3	10	040221	300 000 230
2,40	30	57	2,4	10	040238	300 000 240
2,50	30	57	2,5	10	040245	300 000 250
2,60	30	57	2,6	10	040252	300 000 260
2,70	33	61	2,7	10	040269	300 000 270
2,75	33	61	2,8	10	040276	300 000 275
2,80	33	61	2,8	10	040283	300 000 280
2,90	33	61	2,9	10	040290	300 000 290
3,00	33	61	3,0	10	040306	300 000 300
3,10	36	65	3,1	10	040313	300 000 310
3,20	36	65	3,2	10	040320	300 000 320
3,25	36	65	3,3	10	040337	300 000 325
3,30	36	65	3,3	10	040344	300 000 330
3,40	39	70	3,4	10	040351	300 000 340
3,50	39	70	3,5	10	040368	300 000 350
3,60	39	70	3,6	10	040375	300 000 360
3,70	39	70	3,7	10	040382	300 000 370
3,75	39	70	3,8	10	040399	300 000 375
3,80	43	75	3,8	10	040405	300 000 380
3,90	43	75	3,9	10	040412	300 000 390
4,00	43	75	4,0	10	040429	300 000 400
4,10	43	75	4,1	10	040436	300 000 410
4,20	43	75	4,2	10	040443	300 000 420
4,25	43	75	4,3	10	040450	300 000 425
4,30	47	80	4,3	10	040467	300 000 430

300 HSS DIN 338 STANDARD



DRIVE



EXECUTION

- Right-hand cutting, type N
- High-performance high-speed steel
- Short, cylindrical
- 118° conical section
- Diametral tolerance h8

FOR USE IN



APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

PACKAGING




against
surcharge

[151-152]

[152]

D ø mm	L2 mm	L1 mm	d ø mm	10	FAN 4016707...	12345
4,40	47	80	4,4	10	040474	300 000 440
4,50	47	80	4,5	10	040481	300 000 450
4,60	47	80	4,6	10	040498	300 000 460
4,70	47	80	4,7	10	040504	300 000 470
4,75	47	80	4,8	10	040511	300 000 475
4,80	52	86	4,8	10	040528	300 000 480
4,90	52	86	4,9	10	040535	300 000 490
5,00	52	86	5,0	10	040542	300 000 500
5,10	52	86	5,1	10	040559	300 000 510
5,20	52	86	5,2	10	040566	300 000 520
5,25	52	86	5,3	10	040573	300 000 525
5,30	52	86	5,3	10	040580	300 000 530
5,40	57	93	5,4	10	040597	300 000 540
5,50	57	93	5,5	10	040603	300 000 550
5,60	57	93	5,6	10	040610	300 000 560
5,70	57	93	5,7	10	040627	300 000 570
5,75	57	93	5,8	10	040634	300 000 575
5,80	57	93	5,8	10	040641	300 000 580
5,90	57	93	5,9	10	040658	300 000 590
6,00	57	93	6,0	10	040665	300 000 600
6,10	63	101	6,1	10	040672	300 000 610
6,20	63	101	6,2	10	040689	300 000 620
6,25	63	101	6,3	10	040696	300 000 625
6,30	63	101	6,3	10	040702	300 000 630
6,40	63	101	6,4	10	040719	300 000 640
6,50	63	101	6,5	10	040726	300 000 650
6,60	63	101	6,6	10	040733	300 000 660
6,70	63	101	6,7	10	040740	300 000 670
6,75	69	109	6,8	10	040757	300 000 675
6,80	69	109	6,8	10	040764	300 000 680
6,90	69	109	6,9	10	040771	300 000 690
7,00	69	109	7,0	10	040788	300 000 700
7,10	69	109	7,1	10	040795	300 000 710
7,20	69	109	7,2	10	040801	300 000 720
7,25	69	109	7,3	10	040818	300 000 725
7,30	69	109	7,3	10	040825	300 000 730
7,40	69	109	7,4	10	040832	300 000 740
7,50	69	109	7,5	10	040849	300 000 750
7,60	75	117	7,6	10	040856	300 000 760
7,70	75	117	7,7	10	040863	300 000 770
7,75	75	117	7,8	10	040870	300 000 775
7,80	75	117	7,8	10	040887	300 000 780
7,90	75	117	7,9	10	040894	300 000 790
8,00	75	117	8,0	10	040900	300 000 800
8,10	75	117	8,1	10	040917	300 000 810
8,20	75	117	8,2	10	040924	300 000 820

300 HSS DIN 338 STANDARD



DRIVE



EXECUTION

- Right-hand cutting, type N
- High-performance high-speed steel
- Short, cylindrical
- 118° conical section
- Diametral tolerance h8


FOR USE IN



APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

PACKAGING



against
surcharge

[151-152]

[152]

D ø mm	L2 mm	L1 mm	d ø mm		EAN 4016707...	12345
8,25	75	117	8,3	10	040931	300 000 825
8,30	75	117	8,3	10	040948	300 000 830
8,40	75	117	8,4	10	040955	300 000 840
8,50	75	117	8,5	10	040962	300 000 850
8,60	81	125	8,6	10	040979	300 000 860
8,70	81	125	8,7	10	040986	300 000 870
8,80	81	125	8,8	10	041006	300 000 880
8,90	81	125	8,9	10	041013	300 000 890
9,00	81	125	9,0	10	041020	300 000 900
9,10	81	125	9,1	10	041037	300 000 910
9,20	81	125	9,2	10	041044	300 000 920
9,25	81	125	9,3	10	041051	300 000 925
9,30	81	125	9,3	10	041068	300 000 930
9,50	81	125	9,5	10	041082	300 000 950
9,60	87	133	9,6	10	041099	300 000 960
9,70	87	133	9,7	10	041105	300 000 970
9,80	87	133	9,8	10	041129	300 000 980
9,90	87	133	9,9	10	041136	300 000 990
10,00	87	133	10,0	10	041143	300 001 000
10,20	87	133	10,2	5	041150	300 001 020
10,50	87	133	10,5	5	041167	300 001 050
11,00	94	142	11,0	5	041174	300 001 100
11,50	94	142	11,5	5	041181	300 001 150
12,00	101	151	12,0	5	041198	300 001 200
12,50	101	151	12,5	5	041204	300 001 250
13,00	101	151	13,0	5	041211	300 001 300
13,50	108	160	13,5	5	041228	300 001 350
14,00	108	160	14,0	5	041235	300 001 400
14,50	114	169	14,5	5	041242	300 001 450
15,00	114	169	15,0	5	041259	300 001 500
15,50	120	178	15,5	5	041266	300 001 550
16,00	120	178	16,0	5	041273	300 001 600
16,50	125	184	16,0	5	041280	300 001 650
17,00	125	184	17,0	5	041297	300 001 700
17,50	130	191	17,5	5	041303	300 001 750
18,00	130	191	18,0	5	041310	300 001 800
18,50	135	198	18,5	5	041327	300 001 850
19,00	135	198	19,0	5	041334	300 001 900
20,00	140	205	20,0	5	041358	300 002 000

300 HSS DIN 338 STANDARD



DRIVE



EXECUTION

- Right-hand cutting, type N
- High-performance high-speed steel
- Short, cylindrical
- 118° conical section
- Diametral tolerance h8

FOR USE IN



APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

PACKAGING



against
surcharge

[151-152]

[152]



HSS DIN 338 STANDARD

- The Keil HSS twist drill bits DIN 338 standard have a high elasticity due to heat forming.
- The drill bit has a particularly robust core thickness and distinct hardness resulting in a long tool life. Cold deposition is reduced by the special surface treatment. The achieved torsional strength leads to little danger of breakage, in particular when drilling holes of less than 6 mm diameter.
- This twist drill is the conventional tool for professional use in metal.
- The drills are excellent for machining alloyed and unalloyed steel with a tensile strength up to 800 N/mm², non-iron metal, cast iron and hard plastics.